


SAZJ..(d 4.83~19.05)



| select | Inquiry | 轴承型号 | | 外形尺寸mm | | | | | | | | | | 额定载 | 重 |
|--------|---------|----------------|-------|--------|----------------|---------|----------------|-------|-------|--------------------|----------------|--------|-----|--------|--------|
| | | Bearing number | d | B | d _k | C1 max | d ₂ | G | h | l ₁ min | l ₂ | rs min | a° | 动载荷 kN | 静载荷 kg |
| SAZJ4 | 4.83 | 7.92 | 11.1 | 5.94 | 15.88 | 10-32 | 31.75 | 19.05 | 39.7 | 0.3 | 10 | 3.6 | 3.8 | 0.014 | |
| SAZJ4 | 0.19 | 0.312 | 0.437 | 0.234 | 0.625 | 10-32 | 1.25 | 0.75 | 1.563 | 0.012 | 10 | 3.6 | 3.8 | 0.014 | |
| SAZJ6 | 6.35 | 9.53 | 12.7 | 6.35 | 19.05 | 1/4-28 | 39.67 | 25.4 | 49.2 | 0.3 | 13.5 | 5.4 | 6.6 | 0.018 | |
| SAZJ6 | 0.25 | 0.375 | 0.5 | 0.25 | 0.75 | 1/4-28 | 1.562 | 1 | 1.937 | 0.012 | 13.5 | 5.4 | 6.6 | 0.018 | |
| SAZJ7 | 7.94 | 11.1 | 15.88 | 7.92 | 22.23 | 5/16-24 | 47.63 | 31.75 | 58.72 | 0.3 | 11 | 8.5 | 12 | 0.032 | |
| SAZJ7 | 0.3125 | 0.437 | 0.625 | 0.312 | 0.875 | 5/16-24 | 1.875 | 1.25 | 2.312 | 0.012 | 11 | 8.5 | 12 | 0.032 | |
| SAZJ9 | 9.53 | 12.7 | 18.26 | 9.12 | 25.4 | 3/8-24 | 49.23 | 31.75 | 61.93 | 0.6 | 11 | 11 | 16 | 0.050 | |
| SAZJ9 | 0.375 | 0.5 | 0.719 | 0.359 | 1 | 3/8-24 | 1.938 | 1.25 | 2.438 | 0.024 | 11 | 11 | 16 | 0.050 | |
| SAZJ11 | 11.11 | 14.27 | 20.62 | 10.31 | 28.58 | 7/16-20 | 53.98 | 34.93 | 68.28 | 0.6 | 10.5 | 14 | 21 | 0.068 | |
| SAZJ11 | 0.4375 | 0.562 | 0.812 | 0.406 | 1.125 | 7/16-20 | 2.125 | 1.375 | 2.688 | 0.024 | 10.5 | 14 | 21 | 0.068 | |
| SAZJ12 | 12.7 | 15.88 | 23.81 | 11.5 | 33.32 | 1/2-20 | 61.93 | 38.1 | 78.59 | 0.6 | 10 | 18 | 28 | 0.11 | |
| SAZJ12 | 0.5 | 0.625 | 0.937 | 0.453 | 1.312 | 1/2-20 | 2.438 | 1.5 | 3.094 | 0.024 | 10 | 18 | 28 | 0.11 | |
| SAZJ15 | 15.88 | 19.05 | 28.58 | 12.29 | 38.1 | 5/8-18 | 66.68 | 41.28 | 85.73 | 0.6 | 13 | 23 | 29 | 0.16 | |
| SAZJ15 | 0.625 | 0.75 | 1.125 | 0.484 | 1.5 | 5/8-18 | 2.625 | 1.625 | 3.375 | 0.024 | 13 | 23 | 29 | 0.16 | |
| SAZJ19 | 19.05 | 22.23 | 33.32 | 15.06 | 44.45 | 3/4-16 | 73.03 | 44.45 | 95.25 | 0.6 | 12 | 34 | 44 | 0.26 | |
| SAZJ19 | 0.75 | 0.875 | 1.312 | 0.593 | 1.75 | 3/4-16 | 2.875 | 1.75 | 3.75 | 0.024 | 12 | 34 | 44 | 0.26 | |