


SI...C(d 5□30)



| select | Inquiry | 轴承型号 | | 外形尺寸mm | | | | | | | | | | | | | | | | 额定载 | 重 | |
|--------|---------|----------------|----|--------|----------------|--------------------|----------------|---------|----------------|--------------------|----------------|----------------|----------------|----|----------------|----------------|--------|----|-----|------|-------|--|
| | | Bearing number | d | B | d _k | C ₁ max | d ₂ | G 6H | h ₁ | l ₃ min | l ₄ | l ₅ | l ₇ | W | d ₃ | d ₄ | rs min | a° | 动载荷 | 静载荷 | kg | |
| | | SI5C | 5 | 6 | 10 | 4.5 | 21 | M5 | 30 | 11 | 40.5 | 5 | 11.5 | 10 | 10 | 13 | 0.3 | 13 | 3.6 | 8.1 | 0.021 | |
| | | SI6C | 6 | 6 | 10 | 4.5 | 21 | M6 | 30 | 11 | 40.5 | 5 | 11.5 | 11 | 11 | 13 | 0.3 | 13 | 3.6 | 8.1 | 0.021 | |
| | | SI8C | 8 | 8 | 13 | 6.5 | 24 | M8 | 36 | 15 | 48 | 5 | 13 | 13 | 13 | 16 | 0.3 | 15 | 5.8 | 12.9 | 0.039 | |
| | | SI10C | 10 | 9 | 16 | 7.5 | 29 | M10 | 43 | 20 | 57.5 | 6.5 | 15 | 16 | 16 | 19 | 0.3 | 12 | 8.6 | 17.6 | 0.065 | |
| | | SI12C | 12 | 10 | 18 | 8.5 | 34 | M12 | 50 | 23 | 67 | 7 | 18 | 18 | 19 | 22 | 0.3 | 10 | 11 | 24.5 | 0.096 | |
| | | SI15C | 15 | 12 | 22 | 10.5 | 40 | M14 | 61 | 30 | 81 | 8 | 21 | 21 | 21 | 26 | 0.3 | S | 18 | 36 | 0.16 | |
| | | SI17C | 17 | 14 | 25 | 11.5 | 46 | M16 | 67 | 34 | 90 | 10 | 24 | 27 | 25 | 29 | 0.3 | 10 | 22 | 45 | 0.24 | |
| | | SI20C | 20 | 16 | 29 | 13.5 | 53 | M20x1.5 | 77 | 40 | 103.5 | 10 | 25.5 | 30 | 28 | 34 | 0.3 | 9 | 31 | 60 | 0.35 | |
| | | SI25C | 25 | 20 | 35.5 | 18 | 64 | M24x2 | 94 | 48 | 126 | 12 | 33 | 36 | 35 | 42 | 0.6 | 7 | 51 | 83 | 0.66 | |
| | | SI30C | 30 | 22 | 40.7 | 20 | 73 | M30x2 | 110 | 56 | 146.5 | 15 | 37.5 | 46 | 42 | 50 | 0.6 | 6 | 65 | 110 | 0.98 | |