


# SQ..-RS(d 5□22)



select	Inquiry	轴承型号	外形尺寸Dimensions																额定静重		
		Bearing number	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	l	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	S <sub>1</sub>	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	D <sub>1</sub>	D <sub>2</sub>	D <sub>3</sub>	S <sub>2</sub>	a°	Static load ratings kN	kg
SQ5-RS	M5	9	19	29	8	10	21	7	35	27	4	14	9	11	16	9	25	2.2	0.026		
SQ6-RS	M6	10	20	35.5	11	11	26	8	40	30.5	5	14	10	13	19	11	25	3.5	0.039		
SQ8-RS	M8	12	24	42.5	12	14	31	10	48	36.5	5	17	12.5	16	23	14	25	6.6	0.068		
SQ10-RS	M10x1.25	14	30	50.5	15	17	37	11	57	43.5	6.5	21	15	19	27	17	25	10	0.112		
SQ12-RS	M12x1.25	17	32	57.5	17	19	42	15	66	50.5	6.5	25	17.5	22	31	19	25	16	0.164		
SQ14-RS	M14x1.5	19	38	73.5	22	21.5	56	17	75	57.5	8	26	20	25	35	22	25	19	0.254		
SQ16-RS	M16x1.5	22	44	79.5	23	23.5	60	19	84	64.5	8	32	22	27	39	22	20	26	0.336		
SQ18RS	M18x1.5	23	45	90	25	26.5	68	20	93	71	10	34	25	31	44	27	20	33	0.464		
SQ20RS	M20x1.5	27	50	90	25	27	68	24	99	77	10	35	27.5	34	44	30	20	45	0.538		
SQ22RS	M22x1.5	27	52	95	26	28	70	24	109	84	12	41	30	37	50	32	16	48	0.713		