


# SIZP...N(d 4.83~19.05)



| select  | Inquiry | Bearing No. | Dimensions(mm) |       |                |                    |                |       |                |                    |                |                |                |       |                |                | Basic Load Rating(kN) |      |       | Weight kg |
|---------|---------|-------------|----------------|-------|----------------|--------------------|----------------|-------|----------------|--------------------|----------------|----------------|----------------|-------|----------------|----------------|-----------------------|------|-------|-----------|
|         |         |             | d              | B     | d <sub>k</sub> | C <sub>1</sub> max | d <sub>2</sub> | G     | h <sub>1</sub> | l <sub>3</sub> min | l <sub>4</sub> | l <sub>5</sub> | l <sub>7</sub> | W     | d <sub>3</sub> | d <sub>4</sub> | r <sub>s</sub> min    | a°   | Cr    |           |
| SIZP4N  | 4.83    | 7.92        | ii.i           | 6.35  | 15.88          | 10-32              | 26.97          | 14.27 | 34.93          | 4.75               | 9              | 7.92           | 7.54           | 10.31 | 0.3            | 10             | 3.3                   | 5.38 | 0.015 |           |
| SIZP4N  | 0.19    | 0.312       | 0.437          | 0.25  | 0.625          | 10-32              | 1.062          | 0.562 | 1.375          | 0.187              | 0.354          | 0.312          | 0.297          | 0.406 | 0.012          | 10             | 3.3                   | 5.38 | 0.015 |           |
| SIZP6N  | 6.35    | 9.53        | 12.7           | 7.14  | 19.05          | 1/4-28             | 33.32          | 19.05 | 42.85          | 4.75               | 10.5           | 9.53           | 9.15           | 11.91 | 0.3            | 13             | 6.8                   | 10.9 | 0.025 |           |
| SIZP6N  | 0.25    | 0.375       | 0.5            | 0.281 | 0.75           | 1/4-28             | 1.312          | 0.75  | 1.687          | 0.187              | 0.413          | 0.375          | 0.36           | 0.469 | 0.012          | 13             | 6.8                   | 10.9 | 0.025 |           |
| SIZP7N  | 7.94    | 11.1        | 15.88          | 8.74  | 22.23          | 5/16-24            | 34.93          | 19.05 | 46.02          | 4.75               | 11.7           | 11.1           | 10.72          | 12.7  | 0.3            | 10             | 7.6                   | 12.2 | 0.036 |           |
| SIZP7N  | 3125    | 0.437       | 0.625          | 0.344 | 0.875          | 5/16-24            | 1.375          | 0.75  | 1.812          | 0.187              | 0.461          | 0.437          | 0.422          | 0.5   | 0.012          | 10             | 7.6                   | 12.2 | 0.036 |           |
| SIZP9N  | 9.53    | 12.7        | 18.26          | 10.31 | 25.4           | 3/8-24             | 41.28          | 23.8  | 53.98          | 6.35               | 12.3           | 14.27          | 13.89          | 17.45 | 0.6            | 9              | 11.9                  | 18.2 | 0.061 |           |
| SIZP9N  | 0.375   | 0.5         | 0.719          | 0.406 | 1              | 3/8-24             | 1.625          | 0.937 | 2.125          | 0.25               | 0.484          | 0.562          | 0.547          | 0.687 | 0.024          | 9              | 11.9                  | 18.2 | 0.061 |           |
| SIZP11N | 11.11   | 14.27       | 20.62          | 11.1  | 28.58          | 7/16-20            | 46.02          | 26.97 | 60.33          | 6.35               | 14             | 15.88          | 15.49          | 19.05 | 0.6            | 11             | 17.4                  | 23.8 | 0.081 |           |
| SIZP11N | 0.4375  | 0.562       | 0.812          | 0.437 | 1.125          | 7/16-20            | 1.812          | 1.062 | 2.375          | 0.25               | 0.551          | 0.625          | 0.61           | 0.75  | 0.024          | 11             | 17.4                  | 23.8 | 0.081 |           |
| SIZP12N | 12.7    | 15.88       | 23.81          | 12.7  | 33.32          | 1/2-20             | 53.98          | 30.15 | 70.64          | 6.35               | 16.2           | 19.05          | 18.67          | 22.23 | 0.6            | 9              | 19.9                  | 28.6 | 0.133 |           |
| SIZP12N | 0.5     | 0.625       | 0.937          | 0.5   | 1.312          | 1/2-20             | 2.125          | 1.187 | 2.781          | 0.25               | 0.638          | 0.75           | 0.735          | 0.875 | 0.024          | 9              | 19.9                  | 28.6 | 0.133 |           |
| SIZP15N | 15.88   | 19.05       | 28.58          | 14.27 | 38.1           | 5/8-18             | 63.5           | 38.1  | 82.55          | 7.92               | 18.2           | 22.23          | 21.84          | 25.4  | 0.6            | 11             | 22.9                  | 36.9 | 0.190 |           |
| SIZP15N | 0.625   | 0.75        | 1.125          | 0.562 | 1.5            | 5/8-18             | 2.5            | 1.5   | 3.25           | 0.312              | 0.717          | 0.875          | 0.86           | 1     | 0.024          | 11             | 22.9                  | 36.9 | 0.190 |           |
| SIZP19N | 19.05   | 22.23       | 33.32          | 17.45 | 44.45          | 3/4-16             | 73.03          | 44.45 | 95.25          | 7.92               | 20.9           | 25.4           | 25.02          | 28.58 | 0.6            | 10             | 30.2                  | 48.5 | 0.285 |           |
| SIZP19N | 0.75    | 0.875       | 1.312          | 0.687 | 1.75           | 3/4-16             | 2.875          | 1.75  | 3.75           | 0.312              | 0.823          | 1              | 0.985          | 1.125 | 0.024          | 10             | 30.2                  | 48.5 | 0.285 |           |