

select	Inquiry	Bearing No. Bearing number	Dimensions(mm)												Basic Load Rating(kN)		Weight kg
			d	B	d <sub>k</sub>	C <sub>1max</sub>	d <sub>2</sub>	G	6 <sub>y</sub>	h	l <sub>1min</sub>	l <sub>2</sub>	l <sub>7</sub>	r <sub>smin</sub>	α° ≈	Cr	
SAK5C	5	8	11.112	6	19.5	M5	33	19	42.8	—	0.3	4	3.6	3.9	0.017		
SAK6C	6	9	12.7	7.5	21.2	M6	36	21	46.7	—	0.3	9	4.7	5.2	0.023		
SAK8C	8	12	15.88	9.5	25.5	M8	42	25	54.8	—	0.3	12	7.6	8.2	0.047		
SAK10C	10	14	19.05	11.5	31	M10	48	28	63.6	—	0.3	10	12	15	0.085		
SAK12C	12	16	22.23	12.5	34	M12	54	32	71	—	0.3	12	14	19	0.12		
SAK14C	14	19	25.4	14.5	38	M14	60	36	79	—	0.3	14	19	24	0.17		
SAK16C	16	21	28.58	15.5	42	M16	66	37	87	—	0.3	14	23	29	0.23		
SAK18C	18	23	31.75	17.5	46	M18×1.5	72	41	95	—	0.6	13	29	34	0.31		
SAK20C	20	25	34.93	18.5	50	M20×1.5	78	45	103	27.5	0.6	14	34	40	0.4		