


SAJ...(d 5-22)



select	Inquiry	Bearing No.	Dimensions(mm)										Basic Load Rating(kN)		Weight kg
			d	B	d _k	C1 max	d ₂	G	h	l ₁ min	l ₂	rs min	a°	Cr	
SAJ5	5	8	11.112	7	16	M5	33	20	41	0.3	7	2.3	2.5	0.011	
SAJ6	6	9	12.7	7	18	M6	36	22	45	0.3	11	3.2	4	0.015	
SAJ8	8	12	15.875	9	22	M8	42	25	53	0.3	14	5.3	7.5	0.03	
SAJ10	10	14	19.05	11	26	M10	48	29	61	0.3	12	7.3	10.5	0.048	
SAJ12	12	16	22.225	12	30	M12	54	33	69	0.3	13	8.5	13	0.076	
SAJ14	14	19	25.4	14	34	M14	60	36	77	0.3	14	12	17	0.115	
SAJ16	16	21	28.575	15	38	M16	66	40	85	0.3	15	16.5	21	0.159	
SAJ18	18	23	31.75	17	42	M18x1.5	72	44	93	0.6	14	20	25.5	0.222	
SAJ20	20	25	34.925	18	46	M20x1.5	78	47	101	0.6	14	23	30	0.292	
SAJ22	22	28	38.1	20	50	M22x1.5	84	51	109	0.6	15	27.5	35.5	0.381	